

AC-825IP

Networked Controller

Datasheet



Introduction

The AC-825IP is a 6-door networked access controller suitable for a medium scale to high-scale security system. The controller comes with one onboard expansion slot to connect an additional 6 readers or a maximum of 12 expansion boards via OSDP V2 including secure channel protocol. Using D-805 door expansion boards, a single AC-825IP can handle up to 58 doors and 100,000 users. Driven by Rosslare's AxTraxNG™ or AxTraxPro™ Access Control Management Software – the system provides a modular and expandable solution for commercial and institutional needs.

General Description

The AC-825IP access control unit supports up to 6 doors (In/Out) or up to 12 supported expansions¹. Four additional auxiliary inputs and 2 auxiliary outputs are also on board.

The AC-825IP has TCP/IP communication to the AxTraxNG or AxTraxPro server and has a OSDP bus for expansion and/or reader connectivity.

In addition, the AC-825IP and its expansions can be placed in a ME-1515 lockable metal enclosure.

Main Features

- Up to 58 doors, 100,000 users, and 500,000 history log entries (FIFO) per ACU
- Onboard TCP/IP networking to the AxTraxNG or AxTraxPro server, bidirectional push communication for enhanced data transmission speed and reliability
- Supports SIA Open Supervised Device Protocol (OSDP V2) including OSDP Secured Channel Protocol to let the AC-825IP controller connect to any peripheral device that supports OSDP¹
- A ES 256-bit symmetric data encryption to the AxTraxPro server to make sure the data is secure
- 4 auxiliary inputs and 2 auxiliary outputs
- One onboard expansion slot and an additional 12 expansion boards via OSDP V2 including secure channel protocol (R/S/D/P-805)
 - R-805 – 16 outputs
 - S-805 – 16 inputs
 - D-805 – 4-door expansion
 - P-805 – 16 inputs and 8 outputs
- AC-825IP can be installed in a ME-1515 metal enclosure
 - Holds 2 expansion boards or an AC-825IP board
 - C14 power plug and supports Pull-Safe™ cable locks for secured wiring
 - Built-in tamper and light bar
 - DIN rail mounting option for space saving with no additional enclosure needed
 - Power management board indicates battery and power status

¹AxTraxNG supports 4 Wiegand and 2 OSDP V1 plus up to 12 expansions.

AxTraxPro supports 4 Wiegand and 2 OSDP V2 plus up to 12 expansions or 6 OSDP V2 devices.

Specifications

ELECTRICAL SPECIFICATIONS	AC-825IP	R-805	S-825	D-805	P-805
Enclosure	ME-1515	ME-1515 (up to 2 R/S/D/P expansions)			
Enclosure SMPS	Input: 90 to 265 VAC, 50–60 Hz, Switch mode power management board Output: 12 VDC, 4 A				
PCBA Input Power	12 VDC, 2 A, regulated power management board				
Battery Charger	12 V sealed lead acid (SLA) up to 7 Ah				
OPERATIONAL SPECIFICATIONS					
Relays 5-A, Form-C	6	16	N/A	4	8
Inputs	12	N/A	16	8	16
Readers (Wiegand+OSDP ¹)	6	N/A	N/A	4	N/A
Expansion Port	1	N/A			
Connectivity	TCP/IP OSDP ¹ Wiegand	OSDP ¹			
OPERATIONAL SPECIFICATIONS AC-825IP Only					
Capacity	Up to 100,000 users				
History Event Log Size	Up to 500,000 entries				
Expansion	One onboard expansion slot and an additional 12 expansion boards via OSDP V2 (R/S/D/P-805)				
Time Zones and Groups	256 multi-segment time zones, 64 holidays – each holiday can be of multiple days, Practically unlimited access groups				
Special Features with AxTraxNG/AxTraxPro	Interlock, first-person delay, auto-relock, scheduled outputs operation, 4 programmable site codes, extended unlocked time, fully interconnectedness, car parking management, antipassback (per reader, between readers)				
Secured Communication ²	OSDP V2 including secure channel AES 256-bit symmetric data encryption				
ENVIRONMENTAL SPECIFICATIONS					
Operating Temperature Range	-5°C to 50°C (23°F to 122°F)				
Storage Temperature Range	-25°C to 50°C (-13°F to 122°F)				
Operating Humidity	0 to 85% (non-condensing)				

¹AxTraxNG only supports 4 Wiegand and 2 OSDP V1.

AxTraxPro can supports 4 Wiegand and 2 OSDP V2 or 6 OSDP V2 devices.

²Only available with AxTraxPro.

MECHANICAL SPECIFICATIONS	AC-825IP	R-805	S-825	D-805	P-805
PCBA/Expansion Board Dimensions	224 x 164 mm (8.8 x 6.46 in.)	178 x 87 x 30 mm (7.0 x 3.4 x 1.1 in.)			
PCBA/Expansion Board Weight	400 g (14.1 oz)	230 g (8.1 oz)	150 g (5.3 oz)		200 g (7.1 oz)
Enclosure Dimensions (HxWxD)	346 x 404 x 101 mm (13.6 x 15.9 x 3.9 in.)				
Enclosure Weight	4.6 kg (10.1 lb)				

System Components: AC-825IP is compatible with a range of Rosslare accessories, including a diverse selection of readers and accessories; four expansion boards.

Product Warranty: 2-year limited product warranty



All product names, logos, and brands are property of their respective owners.

DISCLAIMER: The data contained within Rosslare's materials or documentation is intended to provide only general information about products available for purchase from Rosslare Enterprises Ltd. and its associated companies ("Rosslare"). Reasonable efforts have been made to ensure the accuracy of this information. However, it might contain typographic errors, inaccuracies, or omissions that may relate to product descriptions, visual pictures, specifications, and other details. All technical specifications weights, measures and colors shown, are best approximations. Rosslare can not be held responsible and assumes no legal liability for the accuracy or completeness of the information provided. Rosslare reserves the right to change, delete, or otherwise modify the information, which is represented, at any time, without any prior notice.

© 2022 Rosslare Enterprises Ltd. All rights reserved.

For more information regarding support, visit <https://support.rosslaresecurity.com>.